


Starlink Flat High Performance

Designed for mobile applications and challenging environments.




Starlink's flat high-performance is designed for mobility application and challenging environments. With a wide field of view and enhanced GPS capabilities, it can connect to more satellites, allowing for consistent connectivity while on the go. The hardware is designed for a permanent installation and is more resilient to extreme environments.


Starlink Flat High Performance Kit




Dish




Power Supply



Power Supply Mount




Router




Router Mount




Starlink Cable
8m
(26 ft)



Ethernet Cable
5 m
(16.5 ft)



AC Cable (Power Supply)
1.8 m
(6 ft)





AC Cable (Router)
1.8 m
(6 ft)

STARLINK




Starlink Flat High Performance

Starlink Flat High Performance Dish





Antenna	Electronic Phased Array
Field of View	140°
Orientation	Fixed
Dish Weight	5.9 kg / 13 lbs without Cable 6.7 kg / 15 lbs with 8 m / 26.2ft Cable
Environmental Rating	IP56
Operating Temperature	-30°C to 50°C (-22°F to 122°F)
Wind Speed	Survivable: 280 kph+ (174 mph+)
Snow Melt Capability	Up to 75 mm/ hour (3 in / hour)
Power Consumption	Average: 110-150W
Wi-Fi	Dual Band Wi-Fi 5 - 3x3 MIMO
User LAN	RJ45 Cable



Starlink Flat High Performance Router

Wi-Fi Technology	802.11ac Dual Band
Generation	Wi-Fi 5
Radio	Dual Band -3 x 3 MIMO
Operating Temperature	-30°C to 50°C (-22°F to 122°F)
Weight	1 kg (2.2 lbs)
Security	WPA2
Range	Up to 185 m ² (2000 ft ²) *Varies on placement, interference, and materials
Environmental Rating	IP54 - Configured for Indoor Use
Power Indicator	White LED Base of Router
Mesh Compatibility	Compatible with up to 12 Starlink Nodes
Devices	Connect up to 128 devices




STARLINK




Starlink Flat High Performance

Starlink Flat High Performance Router Mount



Starlink Flat High Performance Power Supply Mount





STARLINK



Starlink Flat High Performance

Starlink Flat High Performance Power Supply Unit

Environmental Rating	IP56
Operating Temperature	-30°C to 50°C (-22 to 122°F)
Weight	1.5kg (3lbs)
Grounding	Dedicated Earth Terminal
Power Specifications	100-240V - 6.3A 50 - 60 Hz
Mounting	Included Wall Mount






STARLINK




Starlink Flat High Performance

Starlink Flat High Performance Cable



End	Pin	Wire Color	Pin	End
Dish	A1	Green	A1	Power Supply
	A2	Yellow	A2	
	A3	Blue	A3	
	A4	White	A4	
	B1	Orange	B1	
	B2	Purple	B2	
	B3	Brown	B3	
	B4	Gray	B4	
	B5	Shield / Shell	B5	






STARLINK




Starlink Flat High Performance

Starlink High Performance Router Cable



End	Pin	Ethernet Pin	Wire Color	Pin	End
Wi-Fi	A1, A2	B+	Orange White	A1, A2	Power Supply
	A3, A4	B-	Orange	A3, A4	
	A5, A6	A+	Green White	A5, A6	
	A7, A8	A-	Green	A7, A8	
	B1, B2	-	N / C	B1, B2	
	B3, B4	-	N / C	B3, B4	
	B5	D+	Brown White	B5	
	B6	D-	Brown	B6	
	B7	C-	Blue White	B7	
	B8	C+	Blue	B8	
	B9, B10	-	N / C	B9, B10	
	B11, B12	-	N / C	B11, B12	
	Shield Can		Drain Wire	Shell	






STARLINK




Starlink Flat High Performance

Starlink High Performance Ethernet Cable



End	Pin	Ethernet Pin	Wire Color	Pin	End
RJ45	A1, A2	B+	Orange White	A1, A2	Power Supply
	A3, A4	B-	Orange	A3, A4	
	A5, A6	A+	Green White	A5, A6	
	A7, A8	A-	Green	A7, A8	
	B1, B2	-	N / C	B1, B2	
	B3, B4	-	N / C	B3, B4	
	B5	D+	Brown White	B5	
	B6	D-	Brown	B6	
	B7	C-	Blue White	B7	
	B8	C+	Blue	B8	
	B9, B10	-	N / C	B9, B10	
	B11, B12	-	N / C	B11, B12	
	Shield Can		Drain Wire	Shell	



STARLINK

